



## **Cut- and bendmachine MSBC25-32E, 3x 400V-50Hz**

510.10510

### Features:

- Electrically driven bending machine for rebar.
- Simple and robust design with two adjustable guides.
- The bending plate can rotate both left and right.
- De cutting head is equipped with 2 hardened steel blades that are changeable.
- Angle adjustment by means of stop pins (1 bending angle per direction of rotation).

### Bending tools included:

- 6 bending rollers (Ø50-60-70-80-95mm)
- 3 bending pins
- 1 stirrup bending tool
- 1 small diameter bending pin
- 1 foot pedal

### Technical information:

- RPM: 10
- Motor capacity: 2.2 KW at 3φ 400V/50Hz
- Max. bending capacity at R=650 N/mm<sup>2</sup>: 1×Ø28, 2×Ø20, 3×Ø16mm

- Max. bending capacity at  $R=850 \text{ N/mm}^2$ :  $1 \times \text{Ø}26$ ,  $2 \times \text{Ø}18$ ,  $3 \times \text{Ø}14 \text{ mm}$
- Max. cutting capacity at  $R=650 \text{ N/mm}^2$ :  $1 \times \text{Ø}24$ ,  $2 \times \text{Ø}18$ ,  $3 \times \text{Ø}14 \text{ mm}$
- Max. cutting capacity at  $R=850 \text{ N/mm}^2$ :  $1 \times \text{Ø}22$ ,  $2 \times \text{Ø}16$ ,  $3 \times \text{Ø}12 \text{ mm}$
- L×W×H:  $80 \times 100 \times 83 \text{ cm}$
- Weight: 335 kg