



## **Bending machine MSB74-E, 3x400V-50Hz, 2-speed, with controller**

510.10373

### Features:

- Electrically driven bending machine for rebar.
- Simple and robust design with two adjustable guides.
- The bending plate can rotate both left and right.
- Two bending speeds allow for higher speed when bending thinner diameters.
- Angle adjustment by means of programmable display. Bending shapes consisting of several different bending angles, both positive and negative (up to 20 pieces) in one cycle.
- In addition, a counter is provided to count the number of bends.

### Bending tools included:

- 7 bending rollers (Ø80-95-110-150-200-240-300mm)
- 3 bending pins
- 1 stirrup bending tool
- 1 small diameter bending pin
- 1 foot pedal

### Technical information:

- RPM: 5
- Motor capacity: 7.5 KW at 3 $\phi$  400V/50Hz
- Max. bending capacity at R=650 N/mm<sup>2</sup>: 1 $\times$  $\varnothing$ 60, 2 $\times$  $\varnothing$ 42, 3 $\times$  $\varnothing$ 34mm
- Max. bending capacity at R=850 N/mm<sup>2</sup>: 1 $\times$  $\varnothing$ 50, 2 $\times$  $\varnothing$ 36, 3 $\times$  $\varnothing$ 30mm
- L $\times$ W $\times$ H: 160 $\times$ 116 $\times$ 96cm
- Weight: 1600 kg

Control panel: